

Più slim e leggero, il modello SD400 Lobby è la soluzione ideale per installazioni in ambiti vestibolari





The recycler that took the place of the ATM


The new layout characterized by smaller dimensions and a significant reduction in weight, and the best response to the needs for ever greater installation flexibility,

while offering enhanced performance and advanced functionality

SPECIFICATIONS:

CONTENT MANAGEMENT STORAGE/DISPENSING/RECIRCULATION

Recycling module with 6 drawers that accepts up to to 300 banknotes at a time, for a single operation, composed of:



- Drawers designed for sealing (management outsourced of the ATM)
- Banknote validation sensor in phase deposit and withdrawal
- Recognition, validation and management of cash according to current legislation (cat. L1, L2, L3, L4a, L4b)
- Serial number acquisition and storage
- > Overall capacity of the device: 14,700 banknotes

CHECK DEPOSIT

- Check deposit form with color scanning front/residence (200dpi resolution), presentation on video and image archiving
- Mechanical and electronic alignment system
- Independent final cashier with a capacity of 500 cheques
- Microhole detection

OPERATOR INTERFACE

- > 7 " Touch Screen operator display
- Drawer for captured cards
- Electronic journal

SAFETY

- CEN L/ CEN III / CEN III Gas Ex safes
- Intrinsic safety of the recycler module
- Reinforced shutter with anti-burglary kit
- Mechanical and electronic locks
- Advanced antiskimmer with signal jamming system skimmer detector and assembly control unit
- Integrated banknote staining systems/ anti-gas/ drawer protection barrier
- Anti-blackbox encryption module

SOFTWARE

Microsoft Windows 10
WOSA Standards - XFS

USER INTERFACE

- 19 "Touch Screen Video Privacy Filter - High brightness - Anti-glare
- Vandal-proof EPP PCI keyboard with Privacy shield
- > Extended vandal-proof alphabetic keyboard
- Badge reader
- Paper return device
- Banknote withdrawal/deposit slot with shutter motorized
- Check deposit slot
- Media Entry and Exit indicator
- Ticket printer (80mm)
- ▶ LED lighting
- Audio guide kit for hypo non-selling users
- Camera
- NFC reader
- Qrcode reader



DIMENSIONS

H: 1565 mm - L:555 mm - P: 1169 mm

WEIGHT

CEN L: 640 Kg; CEN III Gas-ex: 770 Kg; CEN IV Gas-ex: 780 Kg

OPERATION

Temperature: -5° +50°

TECHNICAL DETAILS

Power supply: 220 230 V Working frequency: 50 60 Hz Opz. UPS - Uninterruptible Power Supply

REGULATIONS

Co.Ban, EMVco 4.0 Level 1 e 2 Directives: Co.Ban, CAE, ADA, CSA